

REPLACEMENT FILTERS FOR HERDING DUST COLLECTORS

Our proven and high efficiency Sintamatic filters are also available for Herding dust collectors – same form, exact fit. Get your filter from a filter specialist that designs and produces its own filter media and offers service to replace your filters.

Main Features and Advantages

- The rigidity of the Sintamatic element ensures improved cleaning efficiency and savings.
- Sintamatic filters can achieve extremely low emission levels of 1mg/m³ or better.
- Sintamatic filters are used in a variety of applications such as aggregates, carbon black, cement, chemicals, food, glass, graphite, insecticides, minerals, pharmaceuticals, pigments, plastics and many more...

Replacement filters are on stock and ready to ship!



Available Now!

Call our Filtration Specialists
Phone: +32 (0) 16 38 38 11

Cross Reference

Herding Unit Type	Herding P/N	Media	Donaldson P/N	Area (m ²)	Width	Length	Thickness	Max. Temp (°C)
HSL	HSL 900/5	Sintered	2626198	1,17m ²	317 mm	948 mm	42 mm	60
HSL	HSL 900/5	Sintered AS	2626199	1,17 m ²	317 mm	948 mm	42 mm	60
HSL	HSL 900/8	Sintered	2626174	1,9 m ²	496 mm	948 mm	42 mm	60
HSL	HSL 900/8	Sintered AS	2626175	1,9 m ²	496 mm	948 mm	42 mm	60
HSL	HSL 900/12	Sintered	2626176	2,98 m ²	716 mm	948 mm	42 mm	60
HSL	HSL 900/12	Sintered AS	2626177	2,98 m ²	716 mm	948 mm	42 mm	60

Donaldson Europe B.V.B.A.
Research Park Building No. 1303 · Interleuvenlaan 1
B-3001 Leuven · Belgium
Phone: +32 (0) 16 38 38 11
E-mail: IAF-europe@donaldson.com
www.DonaldsonToritDCE.com

Donaldson®
Torit® DCE®

HERDING UNIT TYPE	HERDING P/N	MEDIA	DONALDSON P/N	AREA	WIDTH (mm)	LENGTH (mm)	THICKNESS (mm)	MAX. TEMP (°C)
HSL	HSL 900/18	Sintered	2626169	4,7 m ²	1046 mm	948 mm	42 mm	60
HSL	HSL 900/18	Sintered AS	2626170	4,7 m ²	1046 mm	948 mm	42 mm	60
HSL	HSL 1200/8	Sintered	2626178	2,6 m ²	496 mm	1258 mm	42 mm	60
HSL	HSL 1200/8	Sintered AS	2626179	2,6 m ²	496 mm	1258 mm	42 mm	60
HSL	HSL 1200/12	Sintered	2626180	3,91 m ²	716 mm	1258 mm	42 mm	60
HSL	HSL 1200/12	Sintered AS	2626181	3,91 m ²	716 mm	1258 mm	42 mm	60
HSL	HSL 1200/18	Sintered	2626182	6,3 m ²	1046 mm	1258 mm	42 mm	60
HSL	HSL 1200/18	Sintered AS	2626183	6,3 m ²	1046 mm	1258 mm	42 mm	60
HSL	HSL 1500/8	Sintered	2625950	3,3 m ²	496 mm	1560 mm	42 mm	60
HSL	HSL 1500/8	Sintered AS	2625951	3,3 m ²	496 mm	1560 mm	42 mm	60
HSL	HSL 1500/12	Sintered	2626184	5,02 m ²	716 mm	1560 mm	42 mm	60
HSL	HSL 1500/12	Sintered AS	2626185	5,02 m ²	716 mm	1560 mm	42 mm	60
HSL	HSL 1500/16	Sintered	2626306	6,9 m ²	880 mm	1550 mm	42 mm	60
HSL	HSL 1500/16	Sintered AS	2626307	6,9 m ²	880 mm	1550 mm	42 mm	60
HSL	HSL 1500/18	Sintered AS	2626186	7,9 m ²	1046 mm	1560 mm	42 mm	60
HSL	HSL 1500/18	Sintered	1A43399035 440	7,9 m ²	1046 mm	1560 mm	42 mm	60
Delta	Delta 1500/9 3K	Sintered	2625536	3,3 m ²	500 mm	1500 mm	42 mm	60