



# REPLACEMENT FILTERS FOR PLYMOVENT DUST COLLECTORS

Now our proven and high efficiency Ultra-Web<sup>®</sup> filter media is available for Plymovent cartridge dust collectors – same form, exact fit. Get your filter from a filter specialist that designs its own filter media and offers service to replace your filters.

## Main Features and Advantages

- Ultra-Web<sup>®</sup> is the preferred media for typical applications such as metallization, laser cutting, plasma cutting, welding fumes, shot blasting and many more...
- High filtration efficiency on very fine particulate of < 1 micron
- Increased filter area and greater cost savings



Replacement filters are on stock and ready to ship!

Call our Filtration Specialists  
Phone: **+32 (0) 16 38 38 11**

## Cross Reference

Plymovent Unit Type	Plymovent P/N	Plymovent Media	Donaldson P/N	Dia-meter	Length	Donaldson Filter Area	Donaldson Media
MultiDust <sup>®</sup> Bank	6815-1001	Spunbond Polyester	2625534	324 mm	750 mm*	12.1 m <sup>2</sup>	Ultra-Web <sup>®</sup> Spunbond
MultiDust <sup>®</sup> Bank	6805-1011	Spunbond Polyester, Antistatic	2626346	324 mm	750 mm*	12.1 m <sup>2</sup>	Ultra-Web <sup>®</sup> Spunbond, Antistatic
MultiDust <sup>®</sup> Bank	6850-1011	Spunbond Polyester, PTFE Membrane	2626213	324 mm	750 mm*	12.1 m <sup>2</sup>	Torit-Tex

\*Also available in a different length: 765 mm

Donaldson Europe B.V.B.A.  
Research Park Building No. 1303 · Interleuvenlaan 1  
B-3001 Leuven · Belgium  
Phone: +32 (0) 16 38 38 11  
E-mail: [IAF-europe@donaldson.com](mailto:IAF-europe@donaldson.com)  
[www.donaldson.com](http://www.donaldson.com)

